Univex Model: SRM20 Item#: 4



Exacting Standards, Just Like Yours, since 1948

Project Item Number Quantity

SRM20/NPH20

Features • ½ HP • Variab or any • Chang mixer

Jnivex Corporation

COUNTERTOP

g

- ½ HP Capacitor Start Motor
- Variable Speed Drive: Four fixed speeds or any speed in-between
- Change speeds without having to stop the mixer
- Two-piece, stainless steel, dishwasher safe safety guard
- Heavy-duty stainless steel bowl
- #12 Power Take-Off (PTO) hub on SRM20
- Interlock switches protect operator from injury if safety guard is open or bowl is lowered
- Low voltage protection prevents accidental start-up after power failure
- Hardened alloy gears in transmission
- Durable NSF approved hybrid epoxy / polyester powder coat finish
- Cord and plug

MADE IN THE USA

SRM20/NPH20

20 Quart Countertop Mixers

Models:

- ☐ SRM20 20 qt. Countertop Mixer
- NPH20 20 qt. Countertop Mixer Without PTO Hub







Standard Accessories

- 20 quart stainless steel bowl
- Batter beater
- Wire whip
- Ingredient chute

Optional Accessories

- ☐ 20 quart dough hook
- 15 minute timer
- □ VS9 vegetable slicer attachment
- □ VS9H grater/shredder attachment
- ☐ ALMFC12 meat & food grinder
- Bowl Scraper
- □ Splash / extension ring
- 20 quart pastry knife
- ☐ 12 quart for 20 quart bowl & attachments

Warranty

Two-year, on-site parts & labor warranty

WARRANTY DETAILS

The SRM20 mixer carries a two-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins date of purchase and provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8:00 a.m. and 5:00 p.m. local time, Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential, compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.



Univex Corporation www.univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 USA Tel. (800) 258-6358 Fax: (800) 356-5614 Intl Tel. (603) 893-6191 Int'l Fax: (603) 893-1249 Univex Model: SRM20 Item#: 4



Exacting Standards, Just Like Yours, since 1948

20 Quart Countertop Mixers

SRM20/NPH20



Dimensions

 A)
 Overall height
 35 9/16" (903mm)

 B)
 Base to PTO height
 31 3/8" (797mm)

 C)
 Machine width
 16 7/16" (417mm)

 D)
 Overall width with handle
 20 1/8" (512mm)

 E)
 Depth (leg to leg)
 22 1/2" (572mm)

 F)
 Overall depth
 27 5/16" (694mm)

Shipping Information

Freight Class: 85

Net Weight: 215 lb. (97 kg) Shipping Weight: 250 lb. (114 kg)

Shipping Box Dimensions:

Height: 41" (1041mm) Width: 36 1/2" (927mm) Depth: 23" (584mm)

Cartons are affixed to a pallet. The pallets are heattreated and NELMA approved for international shipping. The weight and dimensions of the pallet are included in the weight and dimensions above.

Capacity: 22 Quarts (20.8 liters)

Motor: 1/2 hp. Capacitor start

Electrical: 115/60/1, 9.4 amps, NEMA plug 5-15P. Also available at an extra cost 208-240/60/1, 220-240/50/1, 230/50/1 (CE), 208-240/60/3, 220/50/3, 380/50/3, 400/50/3 (CE), 440-480/60/3.

Controls: Momentary contact STOP & START buttons and contactor.

Transmission: Univex variable speed transmission with hardened alloy gearing and torque sensing pulleys.

Lubrication: Food grade grease

Finish: NSF approved hybrid epoxy / polyester powder coat

Bowl: Die-drawn stainless steel

Bowl Guard: Heavy-duty, two-piece, stainless steel SwingRing™ safety guards. Swing open for full access to bowl. Removes easily for cleaning, fits in dishwasher. Guard must be attached and closed for mixer to operate. Bowl support interlock provides additional protection.

Speeds: The variable speed transmission not only provides the standard 4 locked-in speeds, but also any in-between speeds

Speed (RPM)	1	2	3	4
Beater Shaft	90	190	305	365
PTO	60	125	200	240

Bowl Lift: Ergonomic hand operated crank, self-locking in top and bottom position.

PTO Hub: Model SRM20 comes with a front-mounted industry standard #12 Power Take-Off (PTO) hub for use with Univex #12 attachments.

Optional Attachments

The following are available at an extra cost:

15 Minute Timer
20qt (22 qt capacity) stainless steel bowl
20qt Aluminum Batter Beater
20qt Aluminum Dough Hook
20qt Wire Whip
Bowl Scraper
Splash / Extension ring
20qt Pastry Knife

20qt Four-Wing whip 12qt Bowl for 20qt mixer 12qt Batter Beater for 20qt mixer 12qt Dough Hook for 20qt mixer 12qt Pastry Knife for 20qt mixer 12qt Four-Wing Whip for 20qt mixer

Optional Accessories:

The following are available at an extra cost:

1000454 Mixer Cover: Heavy-duty clear plastic cover for SRM20

1700800 S-3A Stand: Stainless steel mixer stand with undershelf and locking casters.

1000950 VS9 Vegetable Slicer: 9" vegetable slicer attachment with adjustable knife assembly for use on a #12 PTO hub.

1001050 VS9H Grater / Shredder Attachment: 9" vegetable / cheese shredder attachment with plate holder and 3/16" plate for use on a #12 PTO hub.

1000550 ALMF12 Meat & Food Grinder: Includes cylinder, ring, worm, stainless steel pan, plunger, 3/16" plate and "x" knife. Fits #12 PTO hub.

Printed in the USA 01/07



Univex Corporation www.univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 USA Tel. (800) 258-6358 Fax: (800) 356-5614 Intl Tel. (603) 893-6191 Int'l Fax: (603) 893-1249

TMB Baking Coral PMA Inc. Page: 4-2