PPC-300WP WASHDOWN PORTION CONTROL SCALE



Features

- Complete Stainless Steel Construction
- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate 2,000 Divisions
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units
- Capacities from 4.4 lb to 44 lb (2 kg to 20 kg)
- IP68/65 Waterproof¹



Model	PPC-300 / PPC-300D (dual display)				
	Pound	Kilogram	Ounce	Pound-Ounce*	Max. Tare
PPC-300WP-4	4.4 lb x 0.002 lb	2 kg x 0.001 kg	80 oz x 0.05 oz	5 lb x 0.05 oz	Capacity
PPC-300WP-10	10 lb x 0.005 lb	4 kg x 0.002 kg	160 oz x 0.1 oz	10 lb x 0.1 oz	Capacity
PPC-300WP-22	22 lb x 0.01 lb	10 kg x 0.005 kg	352 oz x 0.2 oz	22 lb x 0.2 oz	Capacity
PPC-300WP-44	44 lb x 0.02 lb	20 kg x 0.01 kg	704 oz x 0.5 oz	44 lb x 0.5 oz	Capacity
Accuracy Class		Class III, 2000 divisions			
Certificate of Conformance		08-041			
Weighing System		Strain gauge load cell			
Platform		9" x 7.625" stainless steel (230 x 194 mm)			
Display		7 segment LDC single display			
Character Size		Character Size: 0.5"x 1.2"5 digits (13.5 x 30 mm) (W x L)			
Housing Material		ABS Plastic			
Power		6 VDC- four "D" size batteries or optional AC adaptor			
Operating Temperatures		14° F to 104° F (-10° C to 40° C)			
Battery Life		1400 hours of continuous use with alkaline batteries			
Function		checkweighing, grading, fixed; unit toggle, function toggle			

PPC-300WP's are manufactured as IP68. If units are opened, they can be closed on-site for an IP65 rating or returned to Yamato for re-sealing to ensure continued IP68 protection. Only Yamato authorized technicians using Yamato approved equipment can assure the integrity of the IP68 protective seal after it has been opened; opening of this unit by anyone else will void the IP68 warranty against internal water damage. *Combined units, such as pound-ounce, are not legal for trade.

Weigh Better Solutions • Weigh Better Support

Yamato Corporation

6306 W. Eastwood Ct. Mequon, WI 53092 Tel: 262.236.0000 Fax: 262.236.0036 **Yamato Corporation**

1775 S. Murray Blvd. Colorado Springs, CO 80916 Tel: 719.591.1500 Fax: 719.591.1045 **Yamato Corporation**

22600 Lambert St., Ste 1205 Lake Forest, CA 92630 Tel: 949.238.4500 Fax 949.455.2711 **Yamato Tech Corporation**

#112-19425 Langley By-Pass Surrey, B.C. V3S 6K1 Canada Tel: 604.533.2338 Fax: 604.533.0827

www.YamatoCorp.com